





MOTOR TECHNICAL DATASHEET



MOTOR SPESIFICATIONS

STEP ANGLE	1.8° ±5%
RATED CURRENT	6.50 A
PHASE NO.	2
HOLDING TORQUE	20.0 N.m
DETENT TORQUE	---
ROTOR INERTIA	210 kg.cm ²
INSULATION CLASS	Class B, 130°C
INSULATION RESISTANCE	100MΩ(500VDC)
IP CODE	IP20
WEIGHT	8400 g. approx
TEMPERATURE RISE	80K Max.
OPERATING TEMPERATURE	-20°C ~ +50°C
STORAGE TEMPERATURE	-20°C ~ +70°C

UNIT: mm
UNLESS OTHERWISE
SPECIFIED TOLERANCES

DEGREES :±0.1°
DIMENSIONS :±0.3 mm
CHAMFER :±5°

CONNECTION TYPE

VOLTAGE


CURRENT

RESISTANCE

INDUCTANCE

HOLDING TORQUE

WIRING DIAGRAMS



BIPOLAR PARALLEL

4.68VDC

6.5A

0.72±10%Ω


12.8±20% mH

20.0N.m

MOTOR LABELS



REAR FLANGE LABEL



SIDE LABEL

R110SM-2000
HYBRID STEPPER MOTOR
DATE : 28 / 12 / 2022 v.003

raxoll
www.raxoll.com